

City Matt

Premium Interior/Exterior Emulsion Paint

DESCRIPTION:

City Matt is an acrylic co-polymer water-based paints of premium quality.

USES:

For interior & exterior uses.

Advantages:

- Excellent hiding power and opacity.
- High resistance to cracks, peeling and chalking.
- Can be applied over plaster: fair-faced concrete, rigid PVC, wood, metal (after proper treatment), old compatible paint ...and many other surfaces.
- Easy to apply.
- High scrub resistance.
- Excellent wet abrasion (high washability resistance).
- Exceptional resistance to extreme weather conditions (humidity, rain, hot temperature, seashore conditions, UV rays, and pollution).
- Environment friendly lead-free formulation.

TECHNICAL PROPERTIES:

Finish	Matt/flat/smooth
Color	White
Density @ 25°C	1.50 ± 0.05 Kg/L
Viscosity @ 25°C	115 - 120 KU
Solid content by Volume	59 ± 2 %
Diluent / thinner	Water
Washability /wet scrubbing	Wet scrub resistance> 8000 strokes or 4000 cycles
Diluent/thinner	Water
Drying time@25 °C & relative Humidity50%	Touch Dry :30 min. Recoat:2-4 hours min. Hard Dry :24 hours
Recommended DFT	30-40 µm

INSTUCTIONS FOR USE:

SURFACE PREPARTION:

Surface must be clean, free from Oil, grease, dirt, chalk...etc.

Old Painted surfaces should be cleaned first from all loose paint and other materials that can affect adhesion.

APPLICATION:

Use City Seal (White) for Priming Purposes and to increase spreading rate.

Mix City Matt thoroughly too Uniform consistency before use.

First coad could be diluted 20% With Water.

Second Coat Could be diluted 20% with water.

Wait 4 hours between each coat for complete drying.

APPLICATION TOOLS:

Brush-Roller-Airless Spray Gun.

SPREADING RAAE:

10-13 m²/L. at the recommended DFT according to porosity preparation of substrate.

CLEANING:

All tools should be cleaned with clean water immediately after use.

Cured material can only be removed mechanically.

PACKAGING:

Available in small containers, gallons, and buckets. Refer to company Price list for more information.

STORAGE&SHELF-LIFE:

18 months in original tightly closed containers away from direct sunlight and excessive heat.



HEALTH AND SAFETY:

Apply under Well Ventilated conditions.

Do not breathe or inhale mist.

Avoid Skin contact. Spillage on the skin should immediately be removed with suitable Cleaner, Soap and Water.

Eyes should be well flushed with water and medical attention to be sought immediately.

FIRE:

City Matt is non-flammable.



Al-Obour Buildings - Salah Salem Road - Nasr City - Cairo - Egypt.
10th Of Ramadan City - EG - P.O.Box: 11811
info@citychem.net



+202 240 456 35
+2010 277 810 11
+20100 663 66 52