

## General Gloss

High quality high gloss enamel paint for interior and exterior applications

### DESCRIPTION:

general gloss is a super quality, high gloss solvent -base enamel paint based on alkyd resins, containing highly selected pigments & additives used as a finish coating for various substrate types.

### USES:

- For interior & exterior use.
- Can be applied over wood, soft & hard boards, concrete, plaster, zinc, metallized steel, new iron and galvanized steel (after special treatment).

### Advantages:

- Excellent hiding Power
- Good color retention.
- Excellent wash ability and weather resistance (temperature, humidity, sunlight, wind & rain).
- Good flow and drying properties.
- Easy to apply.
- Easy to clean.
- Lead free.
- Particularly suitable for wood and steel.

### TECHNICAL PROPERTIES:

Finish Color	Gloss / stretched Available in white and colors.
Density @ 25°C	1.15 ± 0.5Kg/lit
Viscosity @ 25°C	115-120Ku
%Solid content by Wight	64 ± 1 %
Washability/wet scrubbing	Highly washable
Diluent / thinner	White spirit
Drying time at 25 °C & relative Humidity 50%	Touch Dry: 2-3 hours Recoat: 18-24 hours Hard Dry: 24 hours
Recommended DFT	30-40 µm

## INSTRUCTIONS FOR USE:

### SURFACE PREPARTION:

Surface must be dry, clean, free from Oil, grease, dirt, chalk...etc.

On ferrous and non-ferrous metals, use suitable primer like JAC before applying Action.

On painted substrate, wash and leave to dry, make sure that old paints are not loose before preparing the substrate.

### APPLICATION:

Apply General Gloss by using brush or roller

In case of using brush or roller, dilute the protect by 15% white spirit, for first coat.

For Second coat dilute the product by 5-10% white spirit.

In case of using spray gun, dilute the product by 10-20% white spirit depending on the gun nozzle and substrate condition.

### APPLICATION TOOLS:

Brush-Roller-Airless Spray Gun

### SPREADING RAAE:

12-16 m<sup>2</sup>/L. At the recommended DFT in case of white according to porosity preparation of substrate.



### **CLEANING:**

All tools should be cleaned with white spirit immediately after use.

Cured material can only be removed mechanically.

### **PACKAGING:**

Available in small containers, gallons, and buckets. Refer to company Price list for more information.

### **STORAGE&SHELF-LIFE:**

36 months in original tightly closed containers away from direct sunlight and excessive heat.

### **HEALTH AND SAFETY:**

general gloss should not come into contact with the skin or eyes or be swallowed, ensure adequate ventilation and avoid inhalation of vapors.

Wear suitable protective clothing, gloves and eye face protection.

In case of contact with skin, rinse with plenty of clean water, then clean with soap and water.

In case of contact with eyes rinse immediately with plenty of water and seek medical advice.

### **FIRE:**

general gloss is -flammable.

Ensure adequate ventilation. Do not smoke during use.

In the event of fire, extinguish with CO<sub>2</sub> or foam. Do not use a water jet.

