

CITY THICK

PRODUCT DESCRIPTION:

It is an acrylate thickener. It is used in neutral and alkaline systems. Used as thickening agent in aqueous compounds and dispersions.

TECHNICAL PROPERTIES:

<u>Test</u>	<u>Specification</u>	<u>Method</u>
1. Total Solids Content %	15.0 – 17.0	ISO 124
2. pH @25 0C	9.0 – 11.0	ISO 976
3. Viscosity (cps) Brookfield RV S-5@10rpm	15000 - 30000	ISO 1652

Applications:

- The exact required amount must be determined from case to case, so laboratory trials are highly recommended,
- It is highly recommended for Paints, coatings and textile formulation and under water concrete system.
- It can be employed for all commonly used emulsion Resins.
- has a beneficial effect on the storage stability of highly pigmented emulsion paints

HEALTH AND SAFETY

While using the product, gloves and goggles should be worn

STORAGE:

The storage temperature should not fall below + 5 °C and not exceed + 35 °C.

Packing:

1000 Kg 1 MT IBC / 200 kg drums



Al-Obour Buildings - Salah Salem Road - Nasr City - Cairo - Egypt.
10th Of Ramadan City.



info@CityChem.net



[@City_Chem](https://twitter.com/City_Chem)



[City Chem](https://www.facebook.com/CityChem)



+202 240 456 35



+2010 277 810 11



+2010 672 213 44

The Information Herein is Based on Our Present Knowledge and Experiences. This Information Merely Describes the Properties of Our Products but No Guarantee In the legal Sense Shall Be Implied. We Recommend Testing Our Products As To Their Suitability For Your Envisaged Purpose Prior To Use. No Warranties Of Any Kind, Either Express or Implied Including Warranties of Merchantability or Fitness For a Particular Purpose Are Made Regarding Any Products Mentioned Herein and Data or Information That Such Products, Data or Information May Be Used Without Infringing Intellectual Property Rights of Third Parties. We Reserve The Right To Make Any Changes According To Technological Progress or Further Developments. This Copy Replaces All Previous Versions - Printed in Egypt - 2020.

