

## General matt

Matt enamel paint for interior applications

### DESCRIPTION:

general is a synthetic matt paint with maximum hiding power, yellowing resistance and flat enamel with fast drying it can be applied on walls and ceilings directly without priming general is based alkyd resins – Driers – Solvents – additives

### USES:

- For interior use.
- Can be applied over wood, concrete, cement gypsum boards, plaster and steel (after special treatments)

### Advantages:

- Easy to apply
- Good hiding power.
- Good color retention properties
- High spreading rate.
- Good flow and drying properties.
- Lead free.
- Good ease of sandability
- Particularly suitable for wood and steel.

### TECHNICAL PROPERTIES:

Finish Color	Matt viscous liquid Available in white and colors.
Density @ 25°C	1.15 ± 0.1Kg/lit
Viscosity @ 25°C	100±5Ku
%Solid content by Diluent / thinner	73 ± 2 % (by weight) White spirit
Drying time at 25 °C& relative Humidity 50%	Touch dry: 1-2 hours. Hard dry: 12 hours Touch Dry: 2-3 hours
Recommended Dry Film thickness(dft)	50-60 µm
Minimum application temperature	5°C

### INSTUCTIONS FOR USE:

#### SURFACE PREPARTION:

Surface must be dry, clean, free from Oil, grease, dirt, chalk...etc.

On ferrous and non-ferrous metals, use suitable primer like JAC before applying general.

On painted substrate, wash and leave to dry, make sure that old paints are not loose before preparing the substrate.

#### APPLICATION:

Apply General by using brush or roller or a spray gun nozzle 1.8 mm

In case of using brush or roller, dilute the product by 15% white spirit, for first coat.

For Second coat dilute the product by 5-10% white spirit.

In case of using spray gun, dilute the product by 10-20% white spirit depending on the gun nozzle and substrate condition.

#### APPLICATION TOOLS:

Brush-Roller-Airless Spray Gun nozzle 1.8 mm

#### SPREADING RAE:

6-8 m<sup>2</sup>/1 kg. of paint per single coat, At the recommended DFT according to preparation porosity of substrate.



### **CLEANING:**

All tools should be cleaned with white spirit immediately after use.

Cured material can only be removed mechanically.

### **PACKAGING:**

Available in small containers, gallons, and buckets. Refer to company Price list for more information.

### **STORAGE&SHELF-LIFE:**

24 months in original tightly closed containers in cool well – ventilated place, protected from sunlight and heat

### **HEALTH AND SAFETY:**

general should not come into contact with the skin or eyes or be swallowed, ensure adequate ventilation and avoid inhalation of vapors.

Wear suitable protective clothing, gloves and eye face protection.

In case of contact with skin, rinse with plenty of clean water, then clean with soap and water.

In case of contact with eyes rinse immediately with plenty of water and seek medical advice.

### **FIRE:**

general is -flammable.

Ensure adequate ventilation. Do not smoke during use.

In the event of fire, extinguish with CO<sub>2</sub> or foam. Do not use a water jet.

