

ROCK FORM OIL WB

Form work Release Agent

Product Description	A carefully blended combination of refined mineral oils and emulsifying agents, producing a thin film stable release agent.
Uses	ROCK FORM OIL WB when applied to steel, plastic and timber form-work, allows .clean, fast and easy striking. Recommended for Fair - face concrete works
Advantages	ROCK FORM OIL WB provides the following properties:
	■ Good adhesion to the Formwork
	Reduces concrete contamination.
	Non-inflammable.
	All tools can be cleaned with water.
Approval / Standards	Rock Form Oil WB has been tested as per SCAQMD Rule
	.1168. Result : VOC Content < 100 g/l
Technical Data	
Form	Liquid
Colour	White
Density	0.98 kg/l
Packaging	5 Kg and 20 <mark>Kg</mark> pails
	200 kg drums
	Bulk Tanks packing available upon request.
Storage	Store in dry conditions, protected from direct sunlight and frost.
Shelf life	12 months from date of production if stored properly in undamaged and unopened original sealed packing.
Application Details	
Consumption	Timber: ~ 25 m ² /kg
	Steel or plastic: ~ 50 m ² /kg
Application	. One coat application by brush, roller, cloth or spray
	Rock Form Oil WB is ready for use and requires no mixing but adequate stirring is . advisable
	New formwork should be kept dry and after Rock Form Oil WB has been applied, it should be protected from rain and frost
	Do not water the applied coating even when the surface is dry. ROCK FORM OIL WB should be allowed to dry before concreting takes place
Cleaning	Clean all tools, equipment and hands with water













Safety Instruction	s
Safety Precautions	Contact with skin, eyes or mucous membrane may cause irritation. Wear gloves and goggles during the application.
Ecology	Do not dispose of into water or soil but according to local regulations
Toxicity	Non-toxic under the relevant, health and safety codes
Transport	Non-hazardous

















f City Chem



+202 240 456 35 +2010 277 810 11 +20100 663 66 52



