

# ROCK BF 50MM

## SEALANT BACKING MATERIAL AND JOINT FILLER

### DESCRIPTION

Rock BF 50mm material is extruded polyethylene closed-cell foam available in boards, and strips.

### USES

As a backing material (Bond - Breaker) for cold applied joint, and as a joint filler (Neoprene equivalent), due to its highly permanent elasticity, which is most efficient for these purposes.

### CHARACTERISTICS /ADVANTAGES

- Easy to Apply.
- Closed Cell.
- No bond to most sealants.
- Compatible with cold applied sealants.
- Different thicknesses and widths available.
- Highly flexible & compressible.
- Good water resistance.
- Good temperature resistance.

### APPROVALS / STANDARDS

Recovery & compression according to ASTM standard D-545 & D-3575

Compression Ratio Approx. 45% of total thickness.

### PRODUCT INFORMATION

#### CHEMICAL BASE

Extruded closed-cell Polyethylene

#### PACKAGING

Plastic Bag 1000 Meter

#### APPEARANCE / COLOUR

Black.

### SHELF LIFE

5 Years

### STORAGE CONDITIONS

Dry, warm conditions preferred.

### DIMENSIONS

Thickness (mm)	Width (m)	Length (m)
10	1.00	1.00
10	1.10	2.20
15	1.00	1.00
15	1.10	2.20
20	1.00	1.00
20	1.10	2.20
25	1.00	1.00
25	1.00	2.00
50	1.10	2.20

### ECOLOGY, HEALTH AND SAFETY

Transport Non-hazardous.

### TOXICITY

Non-toxic under the relevant Health and Safety Codes.



Al-Obour Building - Salah Salem Road - 1st City - Cairo - Egypt.  
10th Of Ramadan City.



info@CityChem.net



@City\_Chem



City Chem



+202 240 456 35



+2010 277 810 11



+2010 672 213 44

The information herein is based on our present knowledge and experience. It is not intended to be a substitute for professional advice. The information is provided for informational purposes only and does not constitute an offer of any product. The information is provided for informational purposes only and does not constitute an offer of any product. The information is provided for informational purposes only and does not constitute an offer of any product.

